



## THE FOUNTAIN

Our most popular mains connected water fountain is a hardwearing, sturdy unit. It has durable push button operated bubbler and/or Glass Filler. An automatic, self-regulating control is fitted to overcome varying mains pressure. The front panel removes to give instant access to all components and controls. "Hassle Free" filter changes and services can be undertaken without disconnecting the plumbing.

Dispense Options	Bubbler & Swan Neck Bottle Filler, Bubbler, Swan Neck Bottle Filler.
Colours	Grey
Dimensions (mm)	W350 x D350 x H1100
Power Requirements	240V/50Hz
Maximum Running Consumption	230W
Hourly Draw Off	19L/hr @ 10°C
Reservoir Capacity	1.5L

### Cooling System

Stainless Steele 1.5 Litre cold water tank with chilling chamber to meet peak demand. Cooling Capacity 19L per hour to 10°C from water inlet temperature of 26.7°C and ambient temperature of 32.2°C.

### Heating System

Non Toxic, non flammable and environmentally sympathetic R-134a refrigerant. The refrigerant flow is controlled by a capillary tube with no moving parts. To provide for maximum heat exchange (and increase cold water capacity) a suction line is fitted to remove the heated air.

Web: [selsius.co.uk](http://selsius.co.uk) Email: [info@selsius.co.uk](mailto:info@selsius.co.uk)

Selsius North, Suite 23,  
John Buddle Work Village, Buddle Road,  
Newcastle Upon Tyne, NE4 8AW,  
Tel: 0191 2267373

Selsius South, Unit 4 Cambridge West Point,  
Papworth Business Park, Sterling Way,  
Papworth Everard,  
Cambridge, CB23 3WA,  
Tel : 0845 122 2622