

## UNDERSINK CHILLER

The Selsius Limited Under Sink Chiller is ideal for any situation where an 'out of sight' appliance is needed for the provision of freshly chilled filtered water. It is compact, economical and easily installed. Heavy, galvanized steel cabinet construction. To be used along side our range of filter taps.



Dispense Option	N/A
Colours	Silver
Dimensions (mm)	W410 x D210 x H290
Power Requirements	230V/50Hz
Maximum Running Consumption	130w
Cold Temperature	2°C - 12°C
Hourly Draw Off	5L/hr @ 10°C

### Cooling System

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. Refrigerant is controlled by accurately calibrated capillary tube. Highly efficient cooling system. Temperature is controlled by adjustable thermostat, easily accessible at the back of cabinet.

Web: [selsius.co.uk](http://selsius.co.uk) Email: [info@selsius.co.uk](mailto:info@selsius.co.uk)

Selsius North, Suite 23,  
John Buddle Work Village, Buddle Road,  
Newcastle Upon Tyne, NE4 8AW,  
Tel: 0191 2267373

Selsius South, Unit 4 Cambridge West Point,  
Papworth Business Park, Sterling Way,  
Papworth Everard,  
Cambridge, CB23 3WA,  
Tel : 0845 122 2622